

Q.SAFE PRODUCT UPDATES

One of the cornerstones of the Manuli product range, the Q.Safe range of flat face quick couplings was developed with one clear goal in mind - to push the boundaries of what can be achieved by production model quick couplings.

With its exceptional hydrodynamic performance, the **Q.Safe Flat Face** range is recognised globally as the Gold Standard in flat face coupling design. But even perfection can be improved upon, so going forward the Q.Safe Flat Face range will have several significant improvements:

Female connectable under residual pressure - Affecting both the **standard (MQS-F) and heavyduty (MQS-FH)** ranges, this upgrade allows connection to the female coupling with up to 6 MPa of residual pressure still in the system. This is a significant added value which will allow users to save valuable time and effort when changing tools on their appliances.

Zinc Nickel (ZiNi) coating - We have also upgraded the corrosion protection plating on the heavy-duty (MQS-FH), male connectable under pressure (MQS-FP) and screw type (MQS-FS) flat face coupling ranges. Instead of the standard trivalent chrome (Cr3+) plating that is used across the rest of the Q.Safe range, we have upgraded the plating to Zinc Nickel (ZiNi). This upgrade provides up to three times the corrosion resistance of the Cr3+ coating, allowing up to 720 hours to red rust under salt spray conditions.



MQS-F 90° version - Finding the optimum position for quick couplings on vehicles can be tricky, especially on equipment that uses multiple tools, such a skid steers. Sometimes the hose routing necessary for a particular implement just doesn't allow for a standard straight quick coupling. In these cases it is often necessary to change the orientation of the hose connection to the coupling. Q.Safe Flat Face 90° quick couplings are the perfect solution for this type of situation, as well as for those where space is restricted and a straight coupling just won't fit. Available in 3/8" and 1/2" sizes, these couplings are a great addition to the MQS-F product range.

Size			Part Number		Thread
mm	Inch	Dash	Female Coupling	Male Coupling	Thread
10	3/8	06	Q04111301B-06-06	Q03911301B-06-06	9/16" - 18
12.5	1/2	08	Q04111301B-08-08	Q03911301B-08-08	3/4" - 16

If you require any further information about these upgrades to the Q.Safe Flat Face range, please contact your local Manuli representative.



Suite 9A, 111 Piccadilly Manchester, M1 2HY Phone: +44 (0)161 871 1130 Fax: +44 (0)161 247 7862 Email: info@manuli-hydraulics.com